

## TECHNICAL INFORMATION

**Productname :** VALIREX Co 6 Zr 9 D60  
**Date of issue :** November 18, 1998  
**Revision date :** January 25, 2008

**Description** mixture of metal soaps in white spirit D 60 (cobalt - Zirconium)

**Use** drier

Specifications	method of analysis	Minimum	Maximum
metal content (%)	ISO 4619		Co 6 % Zr 9 %
colour			Violet
density (kg/m <sup>3</sup> -20°C)	ISO 2811	1050	1100
viscosity (St-25°C)	ASTM D445-72	-	2
flash point (°C)	ASTM D93-72	62	-
non-volatile matter (%)	1g-1h-150° C	60	-

Some standard methods of analysis have been slightly modified.

**Compatibility** most drying oils, alkyd resins and solvents normally used in surface coating formulations

**Packaging** 200 l (55 gals) and 60 l (15 gals) steel drums, bulk

The safety data sheet is available on request

### Notice

The presented information is accurate to the best of our knowledge, but without any guarantee. Users should satisfy themselves on the suitability of this product for their purposes. If necessary, they can consult our technical service staff.

This issue supersedes and cancels all previous issues concerning this product.

**Umicore Specialty Materials Brugge NV**

Kleine Pathoekeweg 82  
Be-3000 Brugge Belgium

Tel +32.50.320.720  
Fax +32.50.316.047

[www.csm.umicore.com](http://www.csm.umicore.com)  
[info.USMBrugge@eu.umicore.com](mailto:info.USMBrugge@eu.umicore.com)