

## TECHNICAL INFORMATION

**Productname** : **VALIREX Zn 8 % D60**  
**Date of issue** : **January 6, 2006**  
**Revision date** : **January 24, 2008**

**Description** zinc carboxylate in high flash white spirit D60

**Use** drier, additive

Specifications	Method of analysis	minimum	maximum
metal content (%)	ISO 4619	7.8	8.2
Colour (Gardner)	ASTM D1544-68	-	4
density (kg/m <sup>3</sup> -20°C)	ISO 2811	870	920
viscosity (St-25°C)	ASTM D445-72	-	0.5
flash point (°C)	ASTM D93-72	62	-
Non-volatile matter (%)	1g-1h-150°C	36	-

Some standard methods of analysis have been slightly modified.

**Compatibility** most drying oils, alkyd resins and solvents normally used in surface coating formulations

**Packaging** 200 l (55 gals) and 60 l (15 gals) steel drums, bulk

**Note** Use as biocide only in accordance with compulsory legal prescriptions

The safety data sheet is available on request

### Notice

The presented information is accurate to the best of our knowledge, but without any guarantee. Users should satisfy themselves on the suitability of this product for their purposes. If necessary, they can consult our technical service staff.

This issue supersedes and cancels all previous issues concerning this product.