umicore
Cobalt & Specialty Materials

TECHNICAL INFORMATION

Productname : **VALIREX Zr 12 % D60**
Date of issue : **September 25, 2001**
Revision date : **May 29, 2009**

Description zirconium octoate in high flash white spirit D60

Use drier

Specifications	Method of analysis	Minimum	maximum
metal content (%)	ISO 4619	11.7	12.3
Colour (Gardner)	ASTM D1544-68	-	4
density (kg/m3 -20°C)	ISO 2811	950	1010
viscosity (St-25°C)	ASTM D445-72	-	0.2
flash point (°C)	ASTM D93-72	62	-
Non-volatile matter (%)	1g-1h-150°C	35	-

Some standard methods of analysis have been slightly modified.

Compatibility most drying oils, alkyd resins and solvents normally used in surface coating formulations

Packaging 200 l (55 gals) and 60 l (15 gals) steel drums, bulk

The safety data sheet is available on request

Notice

The presented information is accurate to the best of our knowledge, but without any guarantee. Users should satisfy themselves on the suitability of this product for their purposes. If necessary, they can consult our technical service staff.

This issue supersedes and cancels all previous issues concerning this product.

Umicore Specialty Materials Brugge NV
Kleine Pathoekeweg 82
Be-8000 Brugge Belgium
Tel +32.50.320.720
Fax +32.50.316.047
www.csm.umicore.com
info.USMBrugge@eu.umicore.com